

Validate

Print

Help

## Percentage BoQ

<b>Tender Inviting Authority: NHIDCL</b>					
<b>Name of Work: Repair and Maintenance of National Highway (NH 52) between Jamuguri to Bishwanath Chariali (Km. 182.000 to 208.000) (Percentage Rate and Work Order Basis)</b>					
<b>Contract No: NHIDCL/Maint./J-BC/Tender/Tez/2018-19/03</b>					
<b>Bidder Name :</b>					
<b><u>PRICE SCHEDULE</u></b>					
<b>(This BOQ template must not be modified/replaced by the bidder and the same should be uploaded after filling the relevent columns, else the bidder is liable to be rejected for this tender. Bidders are allowed to enter the Bidder Name and Values only )</b>					
<b>NUMBER #</b>	<b>TEXT #</b>	<b>TEXT #</b>	<b>NUMBER</b>	<b>NUMBER #</b>	<b>TEXT #</b>
<b>Sl. No.</b>	<b>Item Description</b>	<b>Units</b>	<b>Estimate d Rate</b>	<b>TOTAL AMOUNT Without Taxes</b>	<b>TOTAL AMOUNT In Words</b>
<b>1</b>	<b>2</b>	<b>5</b>	<b>6</b>	<b>53</b>	<b>55</b>
1	<b>Tack coat:</b> Providing and applying tack coat with bitumen emulsion using emulsion pressurre distributor at the rate of 0.20 kg per sqm on the prepared bituminous/ granular surface cleaned with mechanical broom (including cost of testing of materials at site and laboratory as directed by the deptt.) (I) with Bitumen emulsion CSS-1h (a) Normal bituminous surfaceRate Rs./cum including lead	sqm	0.00	Rs. 1,290,537.50	INR Twelve Lakh Ninety Thousand Five Hundred & Thirty Seven and Paise Fifty Only
2	<b>Bituminous Macadam for pothole filling - 50 mm Thickness:</b> 'Providing and laying bituminous macadam with 100-120 THP hot mix plant producing an average output of 75 tonnes per hour using crushed aggregate of specified grading premix with bituminous binder, transported to site, laid over a previously prepared surface with pave finisher to the required grade, level and alignment and rolled asper Clause 501.60 and 501.7 to achieve the desired compaction.	cum	0.00	Rs. 2,929,412.33	INR Twenty Nine Lakh Twenty Nine Thousand Four Hundred & Twelve and Paise Thirty Three Only

	(Including carriage upto initial lead of 5km from quarry and carriage of mixed materials upto 10km initial lead from mixing plant)- for grading II material				
3	<p><b>Bituminous Macadam for overlay - 50 mm Thickness:</b>  'Providing and laying bituminous macadam with 100-120 THP hot mix plant producing an average output of 75 tonnes per hour using crushed aggregate of specified grading premix with bituminous binder, transported to site, laid over a previously prepared surface with pave finisher to the required grade, level and alignment and rolled asper Clause 501.60 and 501.7 to achieve the desired compaction.  (Including carriage upto initial lead of 5km from quarry and carriage of mixed materials upto 10km initial lead from mixing plant)- for grading II material</p>	cum	0.00	Rs. 19,529,415.50	INR One Crore Ninety Five Lakh Twenty Nine Thousand Four Hundred & Fifteen and Paise Fifty Only
4	<p><b>Bituminous Concrete- 30 mm thickness:</b>  Providing and laying bituminous concrete with 100-120 TPH batch type HMP producing an average output of 75 tonnes per hour using crushed aggregates of specified grading, premixed with bituminous binder@ 5.4 to 5.6 % of mix and filler transporting the hot mix to work site, laying with a hydrostatic paver finisher with sensor control to the reqd. grade, level and alignment,rolling with smooth wheeled,vibratory and tandem rollers to achieve the desired compaction as per MoRT&amp;H cl. no.509. complete in all respect.  (Including carriage upto initial lead of 5km from quarry and carriage of mixed materials upto 10km initial lead from mixing plant)- for grading II material</p>	cum	0.00	Rs. 16,504,954.20	INR One Crore Sixty Five Lakh Four Thousand Nine Hundred & Fifty Four and Paise Twenty Only
5	<p><b>Road Marking:</b>  Road marking with Hot Applied Thermoplastic Compound with Reflectorising Glass Beads on Bituminous Surface -Providing and laying of Hot applied thermoplastic compound 2.5mm thick</p>	sqm	0.00	Rs. 209,030.64	INR Two Lakh Nine Thousand &Thirty and Paise Sixty Four Only

	including reflectorising glass beads @250 gms per sqm, thickness of 2.5mm is exclusive of surface applied glass beads as per IRC:35. the finished surface to be level, uniform and free from streaks and holes.				
<b>Total in Figures</b>				<b>Rs.</b> <b>40,463,350.</b> <b>17</b>	<b>INR Four Crore Four Lakh Sixty Three Thousand Three Hundred &amp; Fifty and Paise Seventeen Only</b>
<b>Quoted Rate in Figures</b>		<b>Select</b>		<b>0.00</b>	<b>INR Zero Only</b>
<b>Quoted Rate in Words</b>		<b>INR Zero Only</b>			

Validate

Print

Help

## Item Wise BoQ

**Tender Inviting Authority: NHIDCL**

**Name of Work: Repair and Maintenance of National Highway (NH 52) between Bishwanath Chariali to Gohpur (Km.208.000 to Km. 265.500)(Percentage Rate and Work Order Basis)**

**Contract No: NHIDCL/Maint./BC-G/Tender/Tez/2018-19/02**

**Bidder Name :**

### PRICE SCHEDULE

**(This BOQ template must not be modified/replaced by the bidder and the same should be uploaded after filling the relevent columns, else the bidder is liable to be rejected for this tender. Bidders are allowed to enter the Bidder Name and Values only )**

NUMBER #	TEXT #	NUMBER #	TEXT #	NUMBER	NUMBER #	TEXT #
Sl. No.	Item Description	Quantity	Units	Estimated Rate	TOTAL AMOUNT Without Taxes	TOTAL AMOUNT In Words
1	2	4	5	6	53	55
1	<b>Tack coat:</b> Providing and applying tack coat with bitumen emulsion using emulsion pressurre distributor at the rate of 0.20 kg per sqm on the prepared bituminous/ granular surface cleaned with mechanical broom (including cost of testing of materials at site and laboratory as directed by the deptt.) (l) with Bitumen emulsion CSS-1h (a) Normal bituminous surfaceRate Rs./cum including lead	105350.00	sqm	12.25	Rs. <b>1,290,537.50</b>	INR Twelve Lakh Ninety Thousand Five Hundred & Thirty Seven and Paise Fifty Only

2	<p><b>Bituminous Macadam for pothole filling - 50 mm Thickness:</b>  'Providing and laying bituminous macadam with 100-120 THP hot mix plant producing an average output of 75 tonnes per hour using crushed aggregate of specified grading premix with bituminous binder, transported to site, laid over a previously prepared surface with pave finisher to the required grade, level and alignment and rolled as per Clause 501.60 and 501.7 to achieve the desired compaction.  (Including carriage upto initial lead of 5km from quarry and carriage of mixed materials upto 10km initial lead from mixing plant)- for grading II material</p>	367.50	cum	7971.19	<b>Rs.</b> <b>2,929,412.33</b>	INR Twenty Nine Lakh Twenty Nine Thousand Four Hundred & Twelve and Paise Thirty Three Only
3	<p><b>Bituminous Macadam for overlay - 50 mm Thickness:</b>  'Providing and laying bituminous macadam with 100-120 THP hot mix plant producing an average output of 75 tonnes per hour using crushed aggregate of specified grading premix with bituminous binder, transported to site, laid over a previously prepared surface with pave finisher to the required grade, level and alignment and rolled as per Clause 501.60 and 501.7 to achieve the desired compaction.  (Including carriage upto initial lead of 5km from quarry and carriage of mixed materials upto 10km initial lead from mixing plant)- for grading II material</p>	2450.00	cum	7971.19	<b>Rs.</b> <b>19,529,415.50</b>	INR One Crore Ninety Five Lakh Twenty Nine Thousand Four Hundred & Fifteen and Paise Fifty Only
4	<p><b>Bituminous Concrete- 30 mm thickness:</b>Providing and laying bituminous concrete with 100-120 TPH batch type HMP producing an average output of 75 tonnes per hour using crushed aggregates of specified grading, premixed with bituminous binder@ 5.4 to 5.6 % of mix and filler transporting the hot mix to work site, laying with a hydrostatic paver finisher with sensor control to the reqd. grade, level and alignment,rolling with smooth wheeled,vibratory and tandem rollers to achieve the desired compaction as per MoRT&amp;H cl. no.509. complete in all respect.(Including carriage upto initial lead of 5km from quarry and carriage of mixed materials upto 10km initial lead from mixing plant)- for grading II material</p>	1470.000	cum	11227.86	<b>Rs.</b> <b>16,504,954.20</b>	INR One Crore Sixty Five Lakh Four Thousand Nine Hundred & Fifty Four and Paise Twenty Only

5	<b>Road Marking:</b> Road marking with Hot Applied Thermoplastic Compound with Reflectorising Glass Beads on Bituminous Surface -Providing and laying of Hot applied thermoplastic compound 2.5mm thick including reflectorising glass beads @250 gms per sqm, thickness of 2.5mm is exclusive of surface applied glass beads as per IRC:35. the finished surface to be level, uniform and free from streaks and holes.	273.0000	sqm	765.68	<b>Rs.</b> <b>209,030.64</b>	INR Two Lakh Nine Thousand &Thirty and Paise Sixty Four Only
<b>Total in Figures</b>					<b>Rs.</b> <b>40,463,350</b> <b>.17</b>	INR Four Crore Four Lakh Sixty Three Thousand Three Hundred & Fifty and Paise Seventeen Only
<b>Quoted Rate in Words</b>						<b>INR Four Crore Four Lakh Sixty Three Thousand Three Hundred &amp; Fifty and Paise Seventeen Only</b>