

**Corrigendum No. I**

**Subject:** Restoration and Repair of NH-08 from km 422.00 to km 455.00 in various reaches (Total Length = 8.91 Km) in the state of Tripura in the FY 2020-21 on item rate basis. **Invitation of Bids-Reg.**

SI No	Reference	Clause No./Item No.	Existing Provision	Modified Provision
1.	BOQ	7	Dense Graded Bituminous Macadam Providing and laying dense graded bituminous macadam with <b>100-120 TPH batch type HMP</b> producing an average output of 75 tonnes per hour using crushed aggregates of specified grading, premixed with bituminous binder @ 4.0 to 4.5 per cent by weight of total mix and filler, transporting the hot mix to work site, laying with a hydrostatic paver finisher with sensor control to the required grade, level and alignment, rolling with smooth wheeled, vibratory and tandem rollers to achieve the desired compaction as per MORT&H specification clause No. 509 complete in all respects. B. Grading II i. With Viscosity Graded Bitumen of VG-30	Dense Graded Bituminous Macadam Providing and laying dense graded bituminous macadam with <b>40-60 TPH HMP</b> producing an average output of 30 tonnes per hour using crushed aggregates of specified grading, premixed with bituminous binder @ 4.0 to 4.5 per cent by weight of total mix and filler, transporting the hot mix to work site, laying with a hydrostatic paver finisher with sensor control to the required grade, level and alignment, rolling with smooth wheeled, vibratory and tandem rollers to achieve the desired compaction as per MORT&H specification complete in all respects. Grading II With Viscosity Graded Bitumen of VG-30
2.	BOQ	8	Bituminous Concrete – Providing and laying bituminous concrete with <b>100-120 TPH batch type hot mix plant</b> producing an average output of 75 tonnes per hour using crushed aggregates of specified grading, premixed with bituminous binder @ 5.4 to 5.6 per cent of mix and filler, transporting the hot mix to work site, laying with a hydrostatic paver finisher with sensor control to the required grade, level and alignment, rolling with smooth wheeled, vibratory and tandem rollers to achieve the desired compaction as per MORT&H specification clause No. 509 complete in all respects. (ii) Grading-II With Viscosity Graded VG-30	Bituminous Concrete – Providing and laying bituminous concrete with <b>40-60 TPH HMP</b> producing an average output of 30 tonnes per hour using crushed aggregates of specified grading, premixed with bituminous binder @ 5.4 to 5.6 per cent of mix and filler, transporting the hot mix to work site, laying with a hydrostatic paver finisher with sensor control to the required grade, level and alignment, rolling with smooth wheeled, vibratory and tandem rollers to achieve the desired compaction as per MORT&H specification complete in all respects. Grading-II With Viscosity Graded VG-30



(Mohd. Asif)  
Manager (P)

For ED(P), RO-Agartala