

CORRIGENDUM-I

Name of Work: Strengthening of the Section from Km 40.300 to Km 42.000 of Silchar-Varingte, NH- 306 in FY 21-22 (Second Call)

Tender ID:2021_NHIDC_627086_1

AMENDMENTS to the BOQ

As per uploaded BOQ				Amended to/To be read as			
Item No.	Description	Unit	Quantity	Item No.	Description	Unit	Quantity
1.08	'Dense Graded Bituminous Macadam (50mm) (Providing and laying dense bituminous macadam with 100-120 TPH batch type HMP producing an average output of 75 tonnes per hour using crushed aggregates of specified grading, premixed with bituminous binder @ 4.0 to 4.5% by weight of total mix and filler transporting the hot mix to work site, laying with a hydrostatic paver finisher with sensor control to the reqd. grade, level and alignment, rolling with smooth wheeled, vibratory and tandem rollers to achieve the desired compaction as per MoRT&H cl. no. 507. complete in all respect. (including carriage up to initial lead of 5.0 km from quarry and carriage of mixed materials up to 10.0 Km initial lead from mixing plant) (Including cost of testing of materials at site and laboratory as directed by the deptt.) (B) With rock dust as filler (refer table 500-9 of MoRT&H specification) (i) with 60/70 or VG-30 grade bitumen (ii) for Grading II (19 mm nominal size)	Sqm	595	1.08	'Dense Graded Bituminous Macadam (50mm) (Providing and laying dense bituminous macadam with 100-120 TPH batch type HMP producing an average output of 75 tonnes per hour using crushed aggregates of specified grading, premixed with bituminous binder @ 4.0 to 4.5% by weight of total mix and filler transporting the hot mix to work site, laying with a hydrostatic paver finisher with sensor control to the reqd. grade, level and alignment, rolling with smooth wheeled, vibratory and tandem rollers to achieve the desired compaction as per MoRT&H cl. no. 507. complete in all respect. (including carriage up to initial lead of 5.0 km from quarry and carriage of mixed materials up to 10.0 Km initial lead from mixing plant) (Including cost of testing of materials at site and laboratory as directed by the deptt.) (B) With rock dust as filler (refer table 500-9 of MoRT&H specification) (i) with 60/70 or VG-30 grade bitumen (ii) for Grading II (19 mm nominal size)	Cum	595
TOTAL AMOUNT Without Taxes in Rs. P				TOTAL AMOUNT With Taxes in Rs. P			

Amended