

A1.1 Clearing and Grubbing									
SOR. NO.	DESCRIPTION	NO. (each)	LENGTH (m)	WIDTH (m)	HEIGHT (m)	Q'TY	UNIT	RATE (Rs)	AMOUNT (Rs)
2.3	Clearing and Grubbing Road Land. (Clearing and grubbing road land including uprooting rank vegetation, grass, bushes, shrubs, saplings and trees girth up to 300 mm, removal of stumps of trees cut earlier and disposal of unserviceable materials and stacking of serviceable material to be used or auctioned up to a lead of 1000 metres including removal and disposal of top organic soil not exceeding 150 mm in thickness.)								
(ii)	By Mechanical Means								
A	In area of light jungle					53	hectare	32,325	1,711,286
B	In area of thorny jungle						hectare	39,635	0
TOTAL						53	hectare		1,711,286

A.1.2 Dismantling of Structures

SOR. NO.	DESCRIPTION	NO. (each)	LENGTH (m)	WIDTH (m)	HEIGHT (m)	Q'TY	UNIT	RATE (Rs)	AMOUNT (Rs)
A.1.2.1	Dismantling of Structures								
2.4	Dismantling of Structures (Dismantling of existing structures like culverts, bridges, retaining walls and other structure comprising of masonry, cement concrete, wood work, steel work, including T&P and scaffolding wherever necessary, sorting the dismantled material, disposal of unserviceable material and stacking the serviceable material with all lifts and lead of 1000 metres)								
(i)	Lime /Cement Concrete								
II	By Mechanical Means for items No. 202(b) & (c)								
A	Cement Concrete Grade M-15 & M-20					290	cum	751	217,994
(iii)	Dismantling Stone Masonry								
B	Rubble stone masonry in cement mortar.					4,019	cum	473	1,901,058
1.1	Loading and unloading of stone boulder/stone aggregates/sand/ kanker/moorum. (Placing tipper at loading point, loading with front end loader, dumping, turning for return trip, excluding time for haulage and return trip)						cum	190	0
1.6	Cost of Haulage Excluding Loading and Unloading For Short Haul for a distance upto 100 km		Lead (km)						
(i)	Surfaced Road		2.5			6,895	tonne.km	10.50	180,996
SUB TOTAL									2,300,047
A.1.2.2	Dismantling of Flexible Pavemets								
2.5	Dismantling of Flexible Pavements (Dismantling of flexible pavements and disposal of dismantled materials up to a lead of 1000 metres, stacking serviceable and unserviceable materials separately)								
II	By Mechanical Means								
A	Bituminous course					1,928	cum	455	877,322
1.1	Loading and unloading of stone boulder/stone aggregates/sand/ kanker/moorum. (Placing tipper at loading point, loading with front end loader, dumping, turning for return trip, excluding time for haulage and return trip)						cum	190	0
1.6	Cost of Haulage Excluding Loading and Unloading For Short Haul for a distance upto 100 km		Lead (km)						
(i)	Surfaced Road		2.5			3,085	tonne.km	10.50	80,984
SUB TOTAL									958,306
TOTAL						1	LS		3,258,353

A1.3 Cutting of Trees									
SOR. NO.	DESCRIPTION	NO. (each)	LENGTH (m)	WIDTH (m)	HEIGHT (m)	Q'TY	UNIT	RATE (Rs)	AMOUNT (Rs)
2.1	Cutting of Trees, including Cutting of Trunks, Branches and Removal (Cutting of trees, including cutting of trunks, branches and removal of stumps, roots, stacking of serviceable material with all lifts and up to a lead of 1000 mtrs and earth filling in the depression/pit.)								
(i)	Girth from 300 mm to 600 mm					565	each	381	215,216
(ii)	Girth from 600 mm to 900 mm					342	each	694	237,642
(iii)	Girth from 900 mm to 1800 mm					110	each	3,802	420,099
(iv)	Girth above 1800 mm					24	each	7,597	180,075
TOTAL						1,041	each		1,053,031

A2.1 Excavation in Soil

SOR. NO.	DESCRIPTION	NO. (each)	LENGTH (m)	WIDTH (m)	HEIGHT (m)	Q'TY	UNIT	RATE (Rs)	AMOUNT (Rs)
3.30	Excavation in Hilly Areas in Ordinary Soil By Mechanical Means (Excavation in ordinary soil in hilly area by mechanical means including cutting and trimming of side slopes and disposing of excavated earth with all lifts and lead .)								
	Case-I : Disposal of cut material with all lifts and lead upto 1000 metres.					23,191	cum	180	4,174,380
	Case-II: Disposing cut material on the valley side						cum	85	0
1.1	Loading and unloading of stone boulder/stone aggregates/sand/kanker/moorum. (Placing tipper at loading point, loading with front end loader, dumping, turning for return trip, excluding time for haulage and return trip)						cum	190	0
1.6	Cost of Haulage Excluding Loading and Unloading For Short Haul for a distance upto 100 km		Lead (km)						
(i)	Surfaced Road		2.5			41,744	tonne.km	10.50	1,095,775
TOTAL						23,191	cum		5,270,155

A2.2 Excavation in Ordinary Rock

SOR. NO.	DESCRIPTION	NO. (each)	LENGTH (m)	WIDTH (m)	HEIGHT (m)	Q'TY	UNIT	RATE (Rs)	AMOUNT (Rs)
A.2.2.1	Excavation in Ordinary Rock not Requiring Blasting								
3.31	Excavation in Hilly Area in Ordinary Rock by Mechanical Means not Requiring Blasting. (Excavation in hilly area in ordinary rock not requiring ballasting by mechanical means including cutting and trimming of slopes and disposal of cut material.)								
	Case-I : Disposal of cut material with all lifts and lead upto 1000 metres.					902,727	cum	276	249,152,514
	Case-II: Disposing cut material on the valley side						cum	146	0
1.1	Loading and unloading of stone boulder/stone aggregates/sand/ kanker/moorum. (Placing tipper at loading point, loading with front end loader, dumping, turning for return trip, excluding time for haulage and return trip)						cum	190	0
1.6	Cost of Haulage Excluding Loading and Unloading For Short Haul for a distance upto 100 km		Lead (km)						
(i)	Surfaced Road		2.5			1,624,908	tonne.km	10.50	42,653,827
SUB TOTAL						902,727	cum		291,806,341
A.2.2.2	Excavation in Ordinary Rock Requiring Blasting								
3.32	Excavation in Hilly Areas in laminated rock (requiring blasting) By Mechanical Means (Excavation for roadway in hilly areas in laminated rock (requiring blasting) which are not suitable for construction of masonry and pavement by drilling, blasting and breaking, trimming of bottom and side slopes in accordance with requirements of lines, grades and cross sections, loading and disposal of cut road with in all lifts and leads upto 1000 metres.)								
	Case-I : Disposal of cut material with all lifts and lead upto 1000 metres.					0	cum	360	0
	Case-II: Disposing cut material on the valley side						cum	269	0
1.1	Loading and unloading of stone boulder/stone aggregates/sand/ kanker/moorum. (Placing tipper at loading point, loading with front end loader, dumping, turning for return trip, excluding time for haulage and return trip)						cum	190	0
1.6	Cost of Haulage Excluding Loading and Unloading For Short Haul for a distance upto 100 km		Lead (km)						
(i)	Surfaced Road		2.5			0	tonne.km	10.50	0
SUB TOTAL						0	cum		0
TOTAL						902,727	cum		291,806,341

A2.3 Excavation in Hard Rock

SOR. NO.	DESCRIPTION	NO. (each)	LENGTH (m)	WIDTH (m)	HEIGHT (m)	QTY	UNIT	RATE (Rs)	AMOUNT (Rs)
3.33	Excavation in Hilly Areas in Hard Rock Requiring Blasting (Excavation in hilly areas in hard rock requiring blasting, by mechanical means including trimming of slopes and disposal of cut material.)								
	Case-I : Disposal of cut material with all lifts and lead upto 1000 metres.					205,558	cum	511	105,039,883
	Case-II: Disposing cut material on the valley side						cum	381	0
1.1	Loading and unloading of stone boulder/stone aggregates/sand/kanker/moorum. (Placing tipper at loading point, loading with front end loader, dumping, turning for return trip, excluding time for haulage and return trip)						cum	190	0
1.6	Cost of Haulage Excluding Loading and Unloading For Short Haul for a distance upto 100 km		Lead (km)						
(i)	Surfaced Road		2.5			370,004	tonne.km	10.50	9,712,592
TOTAL						205,558	cum		114,752,474

A2.4 Excavation for Structures in Soil

SOR. NO.	DESCRIPTION	NO. (each)	LENGTH (m)	WIDTH (m)	HEIGHT (m)	QTY	UNIT	RATE (Rs)	AMOUNT (Rs)
3.11	Excavation for Structures (Earth work in excavation of foundation of structures as per drawing and technical specification, including setting out, construction of shoring and bracing, removal of stumps and other deleterious matter, dressing of sides and bottom, backfilling the excavation earth to the extent required and utilising the remaining earth locally for road work.)								
(i)	Ordinary soil								
B	Mechanical Means (Depth upto 3 m)					1748	cum	79	138,092
TOTAL						1748	cum		138,092

A2.5 Excavation for Structures in Ordinary Rock

SOR. NO.	DESCRIPTION	NO. (each)	LENGTH (m)	WIDTH (m)	HEIGHT (m)	QTY	UNIT	RATE (Rs)	AMOUNT (Rs)
3.11	Excavation for Structures (Earth work in excavation of foundation of structures as per drawing and technical specification, including setting out, construction of shoring and bracing, removal of stumps and other deleterious matter, dressing of sides and bottom, backfilling the excavation earth to the extent required and utilising the remaining earth locally for road work.)								
(ii)	Ordinary rock (not requiring blasting)								
B	Mechanical Means					61,902	cum	105	6,499,710
TOTAL						61,902	cum		6,499,710

A2.6 Excavation for Structures in Hard Rock

SOR. NO.	DESCRIPTION	NO. (each)	LENGTH (m)	WIDTH (m)	HEIGHT (m)	Q'TY	UNIT	RATE (Rs)	AMOUNT (Rs)
3.11	Excavation for Structures (Earth work in excavation of foundation of structures as per drawing and technical specification, including setting out, construction of shoring and bracing, removal of stumps and other deleterious matter, dressing of sides and bottom, backfilling the excavation earth to the extent required and utilising the remaining earth locally for road work.)								
(iii)	Hard rock (requiring blasting)								
A	Manual Means					19,050	cum	889	16,935,450
TOTAL						19,050	cum		16,935,450

A2.7 Embankment Construction

SOR. NO.	DESCRIPTION	NO. (each)	LENGTH (m)	WIDTH (m)	HEIGHT (m)	Q'TY	UNIT	RATE (Rs)	AMOUNT (Rs)
3.15	Construction of Embankment with Material Deposited from Roadway Cutting (Construction of embankment with approved materials deposited at site from roadway cutting and excavation from drain and foundation of other structures graded and compacted to meet requirement of table 300-2)					132,737	cum	189	25,087,293
TOTAL						132,737	cum		25,087,293

A2.8 Scarifying Existing Bituminous Surface

SOR. NO.	DESCRIPTION	NO. (each)	LENGTH (m)	WIDTH (m)	HEIGHT (m)	Q'TY	UNIT	RATE (Rs)	AMOUNT (Rs)
3.13	Scarifying existing bituminous surface to a depth of 50 mm by mechanical means (Scarifying the existing bituminous road surface to a depth of 50 mm and disposal of scarified material with in all lifts and lead upto 1000 metres.)					24,800	sqm	19	471,200
TOTAL						24,800	sqm		471,200

A2.9 Subgrade

SOR. NO.	DESCRIPTION	NO. (each)	LENGTH (m)	WIDTH (m)	HEIGHT (m)	Q'TY	UNIT	RATE (Rs)	AMOUNT (Rs)
3.16	Construction of Subgrade and Earthen Shoulders (Construction of subgrade and earthen shoulders with approved material obtained from borrow pits with all lifts & leads, transporting to site, spreading, grading to required slope and compacted to meet requirement of table No. 300-2)					30,797	cum	473	14,566,981
TOTAL						30,797	cum		14,566,981

A3.1 Granular Sub-base

SOR. NO.	DESCRIPTION	NO. (each)	LENGTH (m)	WIDTH (m)	HEIGHT (m)	Q'TY	UNIT	RATE (Rs)	AMOUNT (Rs)
4.1	Granular Sub-base with Close Graded Material (Table:- 400-1)								
A	Plant Mix Method (Construction of granular sub-base by providing close graded Material, mixing in a mechanical mix plant at OMC, carriage of mixed Material to work site, spreading in uniform layers with motor grader on prepared surface and compacting with vibratory power roller to achieve the desired density, complete as per clause 401)								
(i)	for grading- I Material						cum	3,016	0
(ii)	for grading- II Material					138,786	cum	3,081	427,599,666
(iii)	for grading-III Material						cum	2,852	0
TOTAL						138,786	cum		427,599,666

A3.2 Wet Mix Macadam

SOR. NO.	DESCRIPTION	NO. (each)	LENGTH (m)	WIDTH (m)	HEIGHT (m)	Q'TY	UNIT	RATE (Rs)	AMOUNT (Rs)
4.12	Wet Mix Macadam (Providing, laying, spreading and compacting graded stone aggregate to wet mix macadam specification including premixing the Material with water at OMC in mechanical mix plant carriage of mixed Material by tipper to site, laying in uniform layers with paver in sub- base / base course on well prepared surface and compacting with vibratory roller to achieve the desired density.)					113,595	cum	3,112	353,507,640
TOTAL						113,595	cum		353,507,640

A3.3 Prime Coat

SOR. NO.	DESCRIPTION	NO. (each)	LENGTH (m)	WIDTH (m)	HEIGHT (m)	Q'TY	UNIT	RATE (Rs)	AMOUNT (Rs)
5.1	Prime coat (Providing and applying primer coat with bitumen emulsion on prepared surface of granular Base including clearing of road surface and spraying primer at the rate shown in 500-1 using mechanical means.)								
i) Low Porosity						454,378	sqm	44	19,992,632
TOTAL						454,378	sqm		19,992,632

A3.4 Tack Coat

SOR. NO.	DESCRIPTION	NO. (each)	LENGTH (m)	WIDTH (m)	HEIGHT (m)	Q'TY	UNIT	RATE (Rs)	AMOUNT (Rs)
5.2	Tack coat (Providing and applying tack coat with bitumen emulsion using emulsion pressure distributor at required rate on the prepared bituminous/granular surface cleaned with mechanical broom.)								
i)	Normal Bituminous Surface					507,155	sqm	20	10,143,100
iii)	Granular Surface Treated with Primer						sqm	27	0
TOTAL						507,155	sqm		10,143,100

A3.5 Dense Graded Bituminous Macadam

SOR. NO.	DESCRIPTION	NO. (each)	LENGTH (m)	WIDTH (m)	HEIGHT (m)	Q'TY	UNIT	RATE (Rs)	AMOUNT (Rs)
5.4	Dense Graded Bituminous Macadam (Providing and laying dense bituminous macadam with 100-120 TPH batch type HMP producing an average output of 75 tonnes per hour using crushed aggregates of specified grading, premixed with bituminous binder @ 4.0 to 4.5% by weight of total mix of mix and filler, transporting the hot mix to work site, laying with a hydrostatic paver finisher with sensor control to the required grade, level and alignment, rolling with smooth wheeled, vibratory and tandem rollers to achieve the desired compaction as per MoRTH specification clause No. 507 complete in all respects.)								
(ii)	for Grading II (19 mm nominal size)					44,817	cum	13,335	597,634,695
TOTAL						44,817	cum		597,634,695

A3.6 Bituminous Concrete

SOR. NO.	DESCRIPTION	NO. (each)	LENGTH (m)	WIDTH (m)	HEIGHT (m)	Q'TY	UNIT	RATE (Rs)	AMOUNT (Rs)
5.5	Bituminous Concrete (Providing and laying bituminous concrete with 100-120 TPH batch type hot mix plant producing an average output of 75 tonnes per hour using crushed aggregates of specified grading, premixed with bituminous binder @ 5.4 to 5.6 % of mix and filler, transporting the hot mix to work site, laying with a hydrostatic paver finisher with sensor control to the required grade, level and alignment, rolling with smooth wheeled, vibratory and tandem rollers to achieve the desired compaction as per MoRTH specification clause No. 509 complete in all respects)								
	Case-I Using Bitumen 60/70 grade								
(i)	for Grading-I (13 mm nominal size)					20,104	cum	14,934	300,233,136
TOTAL						20,104	cum		300,233,136

A3.7 Surface Dressing

SOR. NO.	DESCRIPTION	NO. (each)	LENGTH (m)	WIDTH (m)	HEIGHT (m)	Q'TY	UNIT	RATE (Rs)	AMOUNT (Rs)
5.6	Surface Dressing (Providing and laying surface dressing as wearing course in single coat using crushed stone aggregates of specified size on a layer of bituminous binder laid on prepared surface and rolling with 8-10 tonne smooth wheeled steel roller)								
	Case-I: 19 mm nominal chipping size					1,822	sqm	138	251,417
TOTAL						1,822	sqm		251,417

A3.8 Carriage of Materials

SOR. NO.	DESCRIPTION	NO. (each)	LENGTH (m)	WIDTH (m)	HEIGHT (m)	Q'TY	UNIT	RATE (Rs)	AMOUNT (Rs)
-	Cost of Haulage for Granular Sub-base								
	i) Aggregate			138,786	1.28	177,646	cum	359.15	63,801,916
	ii) Sand						cum	286.79	0
	iii) Lime/Filler						cum	3,951.33	0
	iv) Bitumen						tonne	3,119.00	0
-	Cost of Haulage for Wet Mix Macadam								
	i) Aggregate			113,595	1.32	149,945	cum	359.15	53,853,166
	ii) Sand						cum	286.79	0
	iii) Lime/Filler						cum	3,951.33	0
	iv) Bitumen						tonne	3,119.00	0
-	Cost of Haulage for Dense Graded Bituminous Macadam								
	i) Aggregate			44,817	1.44	64,536	cum	359.15	23,178,395
	ii) Sand			44,817	0.45	20,168	cum	286.79	5,783,781
	iii) Lime/Filler			44,817	0.02	896	cum	3,951.33	3,541,738
	iv) Bitumen			44,817	0.1	4,482	tonne	3,119.00	13,978,422
-	Cost of Haulage for Bituminous Concrete								
	i) Aggregate			20,104	1.46	29,352	cum	359.15	10,541,767
	ii) Sand			20,104	0.45	9,047	cum	286.79	2,594,487
	iii) Lime/Filler			20,104	0.02	402	cum	3,951.33	1,588,752
	iv) Bitumen			20,104	0.12	2,412	tonne	3,119.00	7,524,525
	TOTAL					1	LS		186,386,950

A7.1 Traffic Sign

SOR. NO.	DESCRIPTION	NO. (each)	LENGTH (m)	WIDTH (m)	HEIGHT (m)	Q'TY	UNIT	RATE (Rs)	AMOUNT (Rs)
8.4	Retro- reflectorised Traffic signs (Providing and fixing of retro- reflectorised cautionary, mandatory and informatory sign as per IRC :67 made of encapsulated lens type reflective sheeting vide clause 801.3, fixed over aluminium sheeting, 1.5 mm thick supported on a mild steel angle iron post 75 mm x 75 mm x 6 mm firmly fixed to the ground by means of properly designed foundation with M15 grade cement concrete 45 cm x 45 cm x 60 cm, 60 cm below ground level as per approved drawing)								
(i)	90 cm equilateral triangle					9	each	10,001	87,529
(ii)	60 cm equilateral triangle					20	each	6,187	124,091
(iii)	60 cm circular					24	each	8,684	205,840
(iv)	80 mm x 60 mm rectangular					18	each	12,556	228,938
(v)	60 cm x 45 cm rectangular					20	each	8,428	169,038
(vi)	60 cm x 60 cm square					22	each	10,197	223,111
TOTAL						113	each		1,038,548

A7.2 Road Marking

SOR. NO.	DESCRIPTION	NO. (each)	LENGTH (m)	WIDTH (m)	HEIGHT (m)	Q'TY	UNIT	RATE (Rs)	AMOUNT (Rs)
8.13	Road Marking with Hot Applied Thermoplastic Compound with Reflectorising Glass Beads on Bituminous Surface (Providing and laying of hot applied thermoplastic compound 2.5 mm thick including reflectorising glass beads @ 250 gms per sqm area, thickness of 2.5 mm is exclusive of surface applied glass beads as per IRC:35 .The finished surface to be level, uniform and free from streaks and holes.)					11,177	sqm	1,201	13,424,095
TOTAL						11,177	sqm		13,424,095

A7.3 Road Delineator

SOR. NO.	DESCRIPTION	NO. (each)	LENGTH (m)	WIDTH (m)	HEIGHT (m)	Q'TY	UNIT	RATE (Rs)	AMOUNT (Rs)
8.15	Road Delineators (Supplying and installation of delineators (road way indicators, hazard markers, object markers), 80-100 cm high above ground level, painted black and white in 15 cm wide stripes, fitted with 80 x 100 mm rectangular or 75 mm dia circular reflectorised panels at the top, buried or pressed into the ground and confirming to IRC-79 and the drawings.)					40	each	4,336	172,351
TOTAL						40	each		172,351

A7.4 Guard Rail									
SOR. NO.	DESCRIPTION	NO. (each)	LENGTH (m)	WIDTH (m)	HEIGHT (m)	Q'TY	UNIT	RATE (Rs)	AMOUNT (Rs)
8.23	Metal Beam Crash Barrier								
A	Type - A, "W" : Metal Beam Crash Barrier (Providing and erecting a "W" metal beam crash barrier comprising of 3 mm thick corrugated sheet metal beam rail, 70 cm above road/ground level, fixed on ISMC series channel vertical post, 150 x 75 x 5 mm spaced 2 m centre to centre, 1.8 m high, 1.1 m below ground/road level, all steel parts and fitments to be galvanised by hot dip process, all fittings to conform to IS:1367 and IS:1364, metal beam rail to be fixed on the vertical post with a spacer of channel section 150 x 75 x 5 mm, 330 mm long complete as per clause 810)					2,370	metre	5,742	13,610,494
TOTAL						2,370	metre		13,610,494
A7.5 Street Furniture									
SOR. NO.	DESCRIPTION	NO. (each)	LENGTH (m)	WIDTH (m)	HEIGHT (m)	Q'TY	UNIT	RATE (Rs)	AMOUNT (Rs)
8.35	Road Markers/Road Stud with Lense Reflector (Providing and fixing of road stud 100x 100 mm, die cast in aluminium, resistant to corrosive effect of salt and grit, fitted with lense reflectors, installed in concrete or asphaltic surface by drilling hole 30 mm upto a depth of 60 mm and bedded in a suitable bituminous grout or epoxy mortar, all as per BS 873 part 4:1973)					4,965	each	1,317	6,538,841
TOTAL						4,965	each		6,538,841

A8.1 Kilometer Stone (5km)

SOR. NO.	DESCRIPTION	NO. (each)	LENGTH (m)	WIDTH (m)	HEIGHT (m)	Q'TY	UNIT	RATE (Rs)	AMOUNT (Rs)
8.14	Kilo Metre Stone (Reinforced cement concrete M15 grade kilometre stone of standard design as per IRC:8-1980, fixing in position including painting and printing etc)								
(i)	5th kilometre stone (precast)					9	each	5,567	50,753
TOTAL						9	each		50,753

A8.2 Kilometer Stone (1km)

SOR. NO.	DESCRIPTION	NO. (each)	LENGTH (m)	WIDTH (m)	HEIGHT (m)	Q'TY	UNIT	RATE (Rs)	AMOUNT (Rs)
8.14	Kilo Metre Stone (Reinforced cement concrete M15 grade kilometre stone of standard design as per IRC:8-1980, fixing in position including painting and printing etc)								
(ii)	Ordinary Kilometer stone (Precast)					36	each	3,358	121,231
TOTAL						36	each		121,231

A8.3 Kilometer Stone (200m)

SOR. NO.	DESCRIPTION	NO. (each)	LENGTH (m)	WIDTH (m)	HEIGHT (m)	Q'TY	UNIT	RATE (Rs)	AMOUNT (Rs)
8.14	Kilo Metre Stone (Reinforced cement concrete M15 grade kilometre stone of standard design as per IRC:8-1980, fixing in position including painting and printing etc)								
(iii)	Hectometer stone (Precast)					182	each	919	166,895
TOTAL						182	each		166,895

A8.4 Boundary Stone

SOR. NO.	DESCRIPTION	NO. (each)	LENGTH (m)	WIDTH (m)	HEIGHT (m)	Q'TY	UNIT	RATE (Rs)	AMOUNT (Rs)
8.16	Boundary pillar (Reinforced cement concrete M15 grade boundary pillars of standard design as per IRC:25-1967, fixed in position including finishing and lettering but excluding painting)					547	each	862	471,515
TOTAL						547	each		471,515

A8.5 Bus Bay and Road Amenity

[illegible]

A8.6 View Point

[illegible]